**Technical Data** 

## Cosmo | Summary



Collection: Cosmo | Color: Cosmo Anthracite


## **Colors**



Cosmo Beige



Cosmo Grey



Cosmo Brown



Cosmo Anthracite

## **Technical features**

### Natural | R10 A+B | ₹6 mm



• 100×100

### Natural | R10 A+B | x 8 mm



- 120×60
- 60×60
- 60×30

### Structured | R11 A+B+C | \$20 mm



- 120×60
- 100×100
- 60×60

### **Specials**

- Mosaic
- Bullnose
- Step



**40% Raw material from recycling process** products assessed and found to comply with the LEED and BREEAM regulations.



click here for

### Inspiration

Visit the collection webpage in other languages.

# Cosmo

## Product details

Format (cm) Thickness (mm)		120×60 <b>₹</b> 8 mm	100 × 100 <b>₹</b> 20 mm	100 × 100	60 × 60 <b>₹</b> 20 mm	60 × 60 <b>₹</b> 8 mm	60 × 30 <b>3</b> 8 mm	Slabs Variability Index
			+	<del> </del>				The shade variation index
Finishing Skid Resistance		Natural	Structured	Natural	Structured	Natural	Natural	is a rating to determine
	RIIA+B+C	R10 A+B	R11 A+B+C	R10 A+B	R11 A+B+C	R10 A+B	R10 A+B	tile variation between individual pieces of the
Description	-	-	-	-	-	-	-	same color group.
Cosmo Beige	X126450X2	X126450X8	X1010450X2	X1010450X6	X600450X2	X600450X8	X630450X8	V2 slightly different tone
Cosmo Grey	X126451X2	X126451X8	X1010451X2	X1010451X6	X600451X2	X600451X8	X630451X8	V2 slightly different tone
Cosmo Brown	X126452X2	X126452X8	X1010452X2	X1010452X6	X600452X2	X600452X8	X630452X8	V2 slightly different tone
Cosmo Anthracite	X126453X2	X126453X8	X1010453X2	X1010453X6	X600453X2	X600453X8	X630453X8	V2 slightly different tone
Features	CLEAN+	GRIP+	CLEAN+	GRIP+	CLEAN+	GRIP+	GRIP+	
								Note
pieces - box boxes - pallet	1 32	2 36	1 24	2 26	30	32	8 40	
sqm - box	0,72	1,44	1	26	0,72	1,44	1,44	
sqm - pallet	23,04	51,84	24	52	21,6	46,08	57,6	
kg - sqm	45,0226	17,79	45,50	14,06	45,2407	17,41	17,33	
kg - box	32,416	25,618	45,50	28,12	32,573	25,07	24,955	

 $\mathbf{4}$ 

# Cosmo

### Product details

				*		*	*		
									0
Format (cm)		100 × 6,5	60×7	120×30		100×30	60×30		Slabs Variability
Thickness (mm)		<b>¥</b> 6mm	¥8mm	¥8mm		¥6mm	¥8mm		Index
Finishing		Natural	Natural	Natural		Natural	Natural		The shade variation index
	R10 A+B	_	_	R10 A+B		R10 A+B	R10 A+B		is a rating to determine tile variation between
Description		Bullnose	Bullnose	Step with grooves			Step with grooves		individual pieces of the
Description	IVIOSaic 4,7 × 4,7	Dulli lose	Dulli lose	Step with grooves		Step with grooves	Step with grooves		same color group.
Cosmo Beige	X370450X8	X1065450X6	X670450X8	X3213450X8		X3100450X6	X360450X8		V2 slightly different tone
Cosmo Grey	X370451X8	X1065451X6	X670451X8	X3213451X8		X3100451X6	X360451X8		V2 slightly different tone
Cosmo Brown	X370452X8	X1065452X6	X670452X8	X3213452X8		X3100452X6	X360452X8		V2 slightly different tone
Cosmo Anthracite	X370453X8	X1065453X6	X670453X8	X3213453X8		X3100453X6	X360453X8		V2 slightly different tone
									_
	<b>♂</b>			ঠ		3	<b>♂</b>		
Features	GRIP+			GRIP+		GRIP+	GRIP+		
									Note
pieces - box	11	12	10	4		5	6		*Production
boxes - pallet sqm - box	- 0,99	0,78	0,42	- 1,44		1,5	1,08		upon request
sqm - pallet	-	-	-	-		-	-		
kg - sqm	1,57	0,92	0,78	6,4		4,2	3,12		
kg - box	17,27	11,04	7,8	25,6		21	18,72		
ng box	",='	1,51	1,0	20,0	I	1			

 $\mathbf{6}$ 

## **Technical product features**

### Declared values of production

### Compliance with standards

The surfaces complies with the European standards EN 14411 (group B1a) and international standards ISO 13006 Annex G.

- ISO 10545-2 (Determination of dimensions and surface quality)
- ISO 10545-3 (Determination of water absorption)
- ISO 10545-4 (Determination of modulus of rupture and breaking strength)
- ISO 10545-6 (Determination of resistance to deep abrasion for unglazed tiles)
- ISO 10545-8 (Determination of linear thermal expansion)
- ISO 10545-9 (Determination of resistance to thermal shock)
- ISO 10545-12 (Determination of frost resistance)
- ISO 10545-13 (Determination of chemical resistance)
- ISO 10545-14 (Determination of resistance to stains)

And it must also guarantee conformity with:

- DIN 51094 (lightfastness of the colours)
- DIN EN 16165 Annex B (to measure the surfaces suitability for laying in areas where people walk footwear. Defining the "R-value" of the surfaces according to the table below):

```
\alpha < 6° = not classified

6° \leq \alpha \leq 10° = R9

10° < \alpha \leq 19° = R10
```

 $19^{\circ}$ < α ≤  $27^{\circ}$  = R11

 $27^{\circ} < \alpha \le 35^{\circ} = R12$ 

 $\alpha > 35^{\circ} = R13$ 

 DIN EN 16165 - Annex A (to measure the surfaces suitability for laying in areas where people walk barefoot. Given an "A, B and C" value according to the table below):

```
\alpha < 12° = not classified

12° \leq \alpha < 18° = A

18° \leq \alpha < 24° = B (A+B)

\alpha \geq 24° = C (A+B+C)
```

Compliance with these characteristics is checked in accordance with the certified quality management system of the UNI-EN ISO 9001 standard in addition to being guaranteed by the manufacturer.

Porcelaingres surfaces are made with low environmental impact in accordance with LEED\_ BREEAM guidelines by using both new strategies for the continuous improvement of environmental friendliness and the aim of reducing wasting of non-renewable resources, in addition to using natural raw materials commonly found in the environment and recycled materials.

Features		Norms	▲ Required standard	Declared values	
	water absorption	ISO 10545-3	≤ 0,5%	< 0,05%	
	sizes	ISO 10545-2	length and width	± 0,2% max ± 5,0% max ± 0,2% max ± 0,2% max ± 0,2% max	
1	bending strength	ISO 10545-4	≥ 35 N/mm²	> 48N/mm <sup>2</sup> For 20mm slabs: > 42N/mm <sup>2</sup>	
<b>(</b>	resistance to deep abrasion	ISO 10545-6	≤ 175 N/mm³	≤ 140 mm³	
(†)	thermal expansion coefficient	ISO 10545-8	testing method available	7 MK-1	
	thermal shock resistance	ISO 10545-9	testing method available	resistant	
	frost resistance	ISO 10545-12	no sample must show alterations to surface	frost resistance	
	chemical resistance	no sample must show visible signs of chemical attack (acids-bases-additives for pools) except for products containing hydrofluoric acid and derivates.		unaffected	
	stain resistance	ISO 10545-14	unglazed tiles: testing method available	class 5	
0	colour resistance to light	DIN 51094	no sample must show noticeable colour change	no change in brightness or colour	
( <del>X</del> )	skid resistance average coefficient of friction (μ)	DIN EN 16165 Annex B		R10 – natural R11 – strucutred	
	coefficient of medion (µ)	DIN EN 16165 Annex A		A+B A+B+C	

8

### **Certifications**

Sensitivity towards ethycal, environmental, safety and quality concerns

### **Product Certifications:**



**LEED certification:** is a global system used in 40+ countries to check if buildings are environmentally friendly. The LEED (Leadership in Energy and Environmental Design) It evaluates how well a building is sustainable in terms of the environment, society, and economy. The slabs in this tool have over 40% recycled material, following the ISO 14021 standard, ensuring the highest LEED points.

**BREEAM certification** is a widely used global standard that measures how buildings impact the environment. It has strictw rules and checks based on the latest technology and knowledge. The rating system demands certifications based on strict technical parameters and quality control.

You can find the updated list of certified collections at www.porcelaingres.com/downloads/.



**UPEC classification** associated with the QB certification mark attests to the compliance of floor and wall coverings with the technical requirements set out in certification reference documents. It assigns classifications of use indicating that the durability of a product is appropriate for use on specific types of premises.

The list of the certified products is available at <a href="http://evaluation.cstb.fr/">http://evaluation.cstb.fr/</a>



**CE MARK** - It indicates that Porcelaingres products comply with the requirements of 305/2011 UE directive – in particular with regard to health production and the users and consumers' safety – and may thus be freely circulated on the Community market. **For the declarations of conformity of each single product, please refer to:** <a href="https://www.porcelaingres.com/downloads/">www.porcelaingres.com/downloads/</a>.



The **China Compulsory Certificate** mark, commonly known as a **CCC Mark**, is a compulsory safety mark for our Great Format products imported, sold or used in the Chinese market.

The certification is available at www.porcelaingres.com/downloads/.



**EPD (Environmental Product Declaration):** a voluntary type III product declaration, based on analysis of the product life cycle (with a "from cradle to grave" approach) in accordance with the EN 15804 standard. This declaration is drawn up with reference to the guidelines of the UNI EN ISO 14040 standard and the specific PCR (Product Category Rules). This document describes the environmental impact linked to the entire life cycle of a specific quantity of product. Our Company was the first to certify its products (see www.environdec.com) with specific EPD, validated by an independent third-party Body.

The certification is available at www.porcelaingres.com/downloads/.



**GREENGUARD certification** ensures indoor products have minimal emissions of volatile substances for healthier environments. GREENGUARD Gold Certification considers safety for sensitive individuals and approves products for use in places like schools and healthcare facilities. Widely recognized globally in sustainable building programs, it is referenced by The Collaborative for High Performance Schools (CHPS) and Leadership in Energy and Environmental Design (LEED) in the United States.

Certified collections can be found at https://spot.ul.com/.

### **Integrated Management System Certifications:**



**ISO 9001 certification:** for corporate Quality system management. The certification, valid at an international level, concerns corporate management in its entirety, from research and development to production, and from distribution to customer support. This system certifies that the Company has implemented an internal quality management system.

The certification is available at <a href="https://www.porcelaingres.com/downloads/">www.porcelaingres.com/downloads/</a>.



**ISO 50001 certification:** for organizations committed to addressing their impact, conserving resources and improving the bottom line through efficient energy management. The standard specifies the requirements for establishing, implementing, maintaining and improving an energy management system, whose purpose is to enable an organization to follow a systematic approach in achieving continual improvement of energy performance, including energy efficiency, energy security, energy use and consumption.

The certification is available at www.porcelaingres.com/downloads/.

### **Environmental Information and Labels:**



**Declare label:** a badge for construction materials, essentially functioning as a voluntary self-disclosure program. This initiative furnishes details about the material's composition, final assembly locations, lifespan, end-of-life options, and overall adherence to pertinent Living Building Challenge® (LBC) requirements.

Accessible through a complimentary database, Declare® labels prove to be an essential tool for designers and architects, empowering them to specify products aligning with the criteria of key green building standards, including Core Green Building certifications, LBC, LEED, and WELL.

All our materials hold the classification of being "Red List Free," affirming their absence of chemicals listed in the Living Building Challenge's "Red List."

More info available at https://declare.living-future.org/products/ceramic-slabs.



**ISO 14067 certification:** is an international standard that outlines the principles and guidelines for measuring and communicating the carbon footprint of products. This certification focuses on assessing and managing the carbon emissions associated with all stages of a product's life cycle, from raw material extraction through production, distribution, use, and disposal.

The certification is available at www.porcelaingres.com/downloads/.



10 11

## Porcelaingres<sup>®</sup>



### Porcelaingres GmbH

Irisstraße 1 03226 Vetschau – Germany Tel. +49 (0)35433 / 597-0

#### GranitiFiandre spa

Via Radici Nord, 112 42014 Castellarano (RE) – Italy Tel. +39 0536 819611

#### Castellarano Showroom

Via Guido Reni 2 42014 Castellarano (RE) – Italy www.porcelaingres.com info@porcelaingres.com

### **Vetschau Showroom**

Irisstraße 1 03226 Vetschau – Germany www.porcelaingres.com info@porcelaingres.com

A BRAND OF



Search "PORCELAINGRES" on your app store www.porcelaingres.com/pdfapp









Note: Technical Data updated on July 2024

Colors and decors reproductions are approximate. All rights are reserved. Total or partial reproduction of text or illustrations of this catalogue is prohibited and is subject to legal sanctions. Data were updated at the catalogue printing time; therefore, the listed data may alter.