
Technical Data

Native Stone | Summary



Collection: Native Stone | Color: Alver Beige - Fishbone

Inspiration | click here

Visit the collection webpage in other languages.

Colors



Mineral Black



Dusky Greige*

Alver Beige*



Authentic Brown



Mystic Grey*



Decor All colors

Technical features

Natural Plus | R10 A+B | ¥ 6 mm

- 150×75
- 100×100
- 75×75

Natural Plus | R10 A+B | ₹8 mm

- 120×60 + Decor
- 60×60 + Decor
- 60×30
- 60×10 Fishbone

Antislip | R11 A+B+C | ₹8 mm

• 60×60

Antislip | R11 A+B+C | ¥ 20 mm*

- 120×60
- 100×100
- 60×60

Specials

- Mosaic
- Bullnose
- Step



40% Raw material from recycling process products assessed and found to comply with the LEED and BREEAM regulations.

Native Stone

Product details - Part 1 of 2

| | | | | | | | 1 | | | | | I | | |
|--------------------|---------------|----------------|--------------|--------------|---------------|--------------|---|--------------|-----------------|--------------|--------------|--------------|--------------|---|
| | | | | | | | | | | | | - | | Ola ka |
| | | | | | | | | | | | | | | Slabs Variability |
| Format (cm) | 150 × 75 | 120 × 60 | | 120 × 60 | 100 × 100 | | | 75 × 75 | 60 × 60 | | | 60 × 60 | 60 × 30 | Index |
| Thickness (mm) | ¥ 6 mm | ¥ 20 mm | ¥8 mm | ¥8mm | 20 mm | ¥ 6mm | | ¥ 6mm | ± 20 mm | X 8mm | ¥ 8mm | X 8mm | ¥8mm | The shade variation index |
| Finishing | Natural Plus | Antislip | Natural Plus | Natural Plus | Antislip | Natural Plus | | Natural Plus | Antislip | Natural Plus | Antislip | Natural Plus | Natural Plus | is a rating to determine tile variation between |
| Skid Resistance | R10 A+B | R11 A+B+C | R10 A+B | R10 A+B | R11 A+B+C | R10 A+B | | R10 A+B | R11 A+B+C | R10 A+B | R11 A+B+C | R10 A+B | R10 A+B | individual pieces of the |
| Description | - | - | - | Decor | _ | _ | | - | - | - | - | Decor | - | same color group. |
| Cloudy White | X1575430VX6 | | X126430X8 | X1266430X8 | | X1010430X6 | | X7575430VX6 | | X600430X8 | X600430R11X8 | X606430X8 | X630430X8 | V3 different tone |
| Mystic Grey | X1575431VX6 | X126431X2 | X126431X8 | X1266431X8 | X1010431X2 | X1010431X6 | | X7575431VX6 | X600431X2 | X600431X8 | X600431R11X8 | X606431X8 | X630431X8 | V3 different tone |
| Alver Beige | X1575432VX6 | X126432X2 | X126432X8 | X1266432X8 | X1010432X2 | X1010432X6 | | X7575432VX6 | X600432X2 | X600432X8 | X600432R11X8 | X606432X8 | X630432X8 | V3 different tone |
| Dusky Greige | X1575433VX6 | X126433X2 | X126433X8 | X1266433X8 | X1010433X2 | X1010433X6 | | X7575433VX6 | X600433X2 | X600433X8 | X600433R11X8 | X606433X8 | X630433X8 | V3 different tone |
| Mineral Black | X1575434VX6 | | X126434X8 | X1266434X8 | | X1010434X6 | | X7575434VX6 | | X600434X8 | X600434R11X8 | X606434X8 | X630434X8 | V3 different tone |
| Authentic Brown | X1575435VX6 | | X126435X8 | X1266435X8 | | X1010435X6 | | X7575435VX6 | | X600435X8 | X600435R11X8 | X606435X8 | X630435X8 | V3 different tone |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | Note |
| pieces - box | 2 | 1 | 2 | 2 | 1 | 2 | | 3 | 2 | 4 | 4 | 4 | 8 | |
| boxes - pallet | 30 | 32 | 36 | 36 | 24 | 26 | | 40 | 30 | 32 | 32 | 32 | 40 | |
| sqm - box | 2,25 | 0,72 | 1,44 | 1,44 | 1 | 2 | | 1,688 | 0,72 | 1,44 | 1,44 | 1,44 | 1,44 | |
| sqm - pallet | 67,5 | 23,04 | 51,84 | 51,84 | 24 | 52 | | 67,52 | 21,6 | 46,08 | 46,08 | 46,08 | 57,6 | |
| kg - sqm | 13,7067 | 45,0226 | 17,79 | 17,79 | 45,50 | 14,06 | | 13,7915 | 45,2407 | 17,41 | 17,41 | 17,41 | 17,33 | |
| kg - box | 30,84 | 32,416 | 25,618 | 25,618 | 45,50 | 28,12 | | 23,273 | 32,573 | 25,07 | 25,07 | 25,07 | 24,955 | |

 $oldsymbol{4}$

Native Stone

Product details - Part 2 of 2

| | | * | | | | | * | * | * | * | * | |
|--------------------|--------------|------------------|------------------|------------------|--------------|--------------|-------------------|-------------------|-------------------|-------------------|-------------------|--|
| | | | | | | | | | | | | Slabs Variability |
| Format (cm) | 60 × 10 | 30 × 30 | 30 × 30 | 100 × 6,5 | 75 × 6,5 | 60 × 7 | 150 × 37,5 | 120 × 30 | 100 × 30 | 75 × 37,5 | 60 × 30 | Index |
| Thickness (mm) | X 8mm | x 8mm | X 8mm | X 6mm | X 6mm | x 8mm | X 6mm | ¥8mm | x 6mm | ¥6mm | X 8mm | The shade variation index |
| Finishing | Natural Plus | Natural Plus | Natural Plus | Natural Plus | Natural Plus | Natural Plus | Natural Plus | Natural Plus | Natural Plus | Natural Plus | Natural Plus | is a rating to determine tile variation between |
| Skid Resistance | R10 A+B | R10 A+B | R10 A+B | - | - | - | R10 A+B | individual pieces of the |
| Description | Fishbone | Mosaic 3,1 × 3,1 | Mosaic 4,7 × 4,7 | Bullnose | Bullnose | Bullnose | Step with grooves | same color group. |
| Cloudy White | X160430X8 | X373430X8 | X370430X8 | X1065430X6 | X765430VX6 | X670430X8 | X3715430VX6 | X3213430X8 | X3100430X6 | X3775430VX6 | X360430X8 | V3 different tone |
| Mystic Grey | X160431X8 | X373431X8 | X370431X8 | X1065431X6 | X765431VX6 | X670431X8 | X3715431VX6 | X3213431X8 | X3100431X6 | X3775431VX6 | X360431X8 | V3 different tone |
| Alver Beige | X160432X8 | X373432X8 | X370432X8 | X1065432X6 | X765432VX6 | X670432X8 | X3715432VX6 | X3213432X8 | X3100432X6 | X3775432VX6 | X360432X8 | V3 different tone |
| Dusky Greige | X160433X8 | X373433X8 | X370433X8 | X1065433X6 | X765433VX6 | X670433X8 | X3715433VX6 | X3213433X8 | X3100433X6 | X3775433VX6 | X360433X8 | V3 different tone |
| Mineral Black | X160434X8 | X373434X8 | X370434X8 | X1065434X6 | X765434VX6 | X670434X8 | X3715434VX6 | X3213434X8 | X3100434X6 | X3775434VX6 | X360434X8 | V3 different tone |
| Authentic Brown | X160435X8 | X373435X8 | X370435X8 | X1065435X6 | X765435VX6 | X670435X8 | X3715435VX6 | X3213435X8 | X3100435X6 | X3775435VX6 | X360435X8 | V3 different tone |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | Note |
| pieces - box | 15 | 11 | 11 | 12 | 15 | 10 | 2 | 4 | 5 | 3 | 6 | *Production |
| boxes - pallet | 60 | - | - | - | - | - | - | - | - | - | - | upon request |
| sqm - box | 0,9 | 0,99 | 0,99 | 0,78 | 0,731 | 0,42 | 1,125 | 1,44 | 1,5 | 0,844 | 1,08 | |
| sqm - pallet | 54 | - | - | - | - | - | - | - | - | - | - | |
| kg - sqm | 17,33 | 1,57 | 1,57 | 0,92 | 0,69 | 0,78 | 7,91 | 6,4 | 4,2 | 3,96 | 3,12 | |
| kg - box | 15,597 | 17,27 | 17,27 | 11,04 | 10,35 | 7,8 | 15,82 | 25,6 | 21 | 11,88 | 18,72 | |

Technical product features

Declared values of production

Compliance with standards

The surfaces complies with the European standards EN 14411 (group B1a) and international standards ISO 13006 Annex G.

- ISO 10545-2 (Determination of dimensions and surface quality)
- ISO 10545-3 (Determination of water absorption)
- ISO 10545-4 (Determination of modulus of rupture and breaking strength)
- ISO 10545-6 (Determination of resistance to deep abrasion for unglazed tiles)
- ISO 10545-8 (Determination of linear thermal expansion)
- ISO 10545-9 (Determination of resistance to thermal shock)
- ISO 10545-12 (Determination of frost resistance)
- ISO 10545-13 (Determination of chemical resistance)
- ISO 10545-14 (Determination of resistance to stains)

And it must also guarantee conformity with:

- DIN 51094 (lightfastness of the colours)
- DIN EN 16165 Annex B (to measure the surfaces suitability for laying in areas where people
 walk footwear. Defining the "R-value" of the surfaces according to the table below):

```
\alpha < 6° = not classified
```

 $6^{\circ} \le \alpha \le 10^{\circ} = R9$

 $10^{\circ} < \alpha \le 19^{\circ} = R10$

 19° < α ≤ 27° = R11

 $27^{\circ} < \alpha \le 35^{\circ} = R12$

 $\alpha > 35^{\circ} = R13$

 DIN EN 16165 - Annex A (to measure the surfaces suitability for laying in areas where people walk barefoot. Given an "A, B and C" value according to the table below):

 α < 12° = not classified

 $12^{\circ} \le \alpha < 18^{\circ} = A$

 $18^{\circ} \le \alpha < 24^{\circ} = B (A+B)$

 $\alpha \ge 24^{\circ} = C (A+B+C)$

Compliance with these characteristics is checked in accordance with the certified quality management system of the UNI-EN ISO 9001 standard in addition to being guaranteed by the manufacturer.

Porcelaingres surfaces are made with low environmental impact in accordance with LEED_ BREEAM guidelines by using both new strategies for the continuous improvement of environmental friendliness and the aim of reducing wasting of non-renewable resources, in addition to using natural raw materials commonly found in the environment and recycled materials.

| Featur | res | Norms | ▲ Required standard | Declared values | |
|----------------|---|-------------------------|---|--|--|
| | water absorption | ISO 10545-3 | ≤ 0,5% | < 0,05% | |
| | sizes | ISO 10545-2 | length and width ± 0,6% max thickness ± 5,0% max linearity ± 0,5% max wedging ± 0,6% max warpage ± 0,5% max | ± 0,2% max ± 5,0% max ± 0,2% max ± 0,2% max ± 0,2% max | |
| 1 | bending strength | ISO 10545-4 | ≥ 35 N/mm² | > 48N/mm² For 20mm slabs: > 42N/mm² | |
| (E O B) | resistance to deep abrasion | ISO 10545-6 | ≤ 175 N/mm³ | ≤ 140 mm³ | |
| (← •→) | thermal expansion coefficient | ISO 10545-8 | testing method available | 7 MK-1 | |
| | thermal shock resistance | ISO 10545-9 | testing method available | resistant | |
| | frost resistance | ISO 10545-12 | no sample must show alterations to surface | frost resistance | |
| | chemical resistance | ISO 10545-13 | no sample must show visible signs of chemical attack (acids-bases-additives for pools) except for products containing hydrofluoric acid and derivates. | unaffected | |
| | stain resistance | ISO 10545-14 | unglazed tiles: testing method available | class 5 | |
| 0 | colour resistance to light | DIN 51094 | no sample must show noticeable colour change | no change in brightness or colour | |
| | skid resistance average coefficient of friction (µ) | DIN EN 16165 Annex B | | R10 R11 | |
| W | осеннови от писион (µ) | DIN EN 16165 Annex A | | A+B A+B+C | |

Certifications

Sensitivity towards ethycal, environmental, safety and quality concerns

Product Certifications:



LEED certification: is a global system used in 40+ countries to check if buildings are environmentally friendly. The LEED (Leadership in Energy and Environmental Design) It evaluates how well a building is sustainable in terms of the environment, society, and economy. The slabs in this tool have over 40% recycled material, following the ISO 14021 standard, ensuring the highest LEED points.

BREEAM certification is a widely used global standard that measures how buildings impact the environment. It has strictw rules and checks based on the latest technology and knowledge. The rating system demands certifications based on strict technical parameters and quality control.

You can find the updated list of certified collections at www.porcelaingres.com/downloads/.



UPEC classification associated with the QB certification mark attests to the compliance of floor and wall coverings with the technical requirements set out in certification reference documents. It assigns classifications of use indicating that the durability of a product is appropriate for use on specific types of premises.

The list of the certified products is available at http://evaluation.cstb.fr/



CE MARK - It indicates that Porcelaingres products comply with the requirements of 305/2011 UE directive – in particular with regard to health production and the users and consumers' safety – and may thus be freely circulated on the Community market. **For the declarations of conformity of each single product, please refer to:** www.porcelaingres.com/downloads/.



The **China Compulsory Certificate** mark, commonly known as a **CCC Mark**, is a compulsory safety mark for our Great Format products imported, sold or used in the Chinese market.

The certification is available at www.porcelaingres.com/downloads/.



EPD (Environmental Product Declaration): a voluntary type III product declaration, based on analysis of the product life cycle (with a "from cradle to grave" approach) in accordance with the EN 15804 standard. This declaration is drawn up with reference to the guidelines of the UNI EN ISO 14040 standard and the specific PCR (Product Category Rules). This document describes the environmental impact linked to the entire life cycle of a specific quantity of product. Our Company was the first to certify its products (see www.environdec.com) with specific EPD, validated by an independent third-party Body.

The certification is available at www.porcelaingres.com/downloads/.



GREENGUARD certification ensures indoor products have minimal emissions of volatile substances for healthier environments. GREENGUARD Gold Certification considers safety for sensitive individuals and approves products for use in places like schools and healthcare facilities. Widely recognized globally in sustainable building programs, it is referenced by The Collaborative for High Performance Schools (CHPS) and Leadership in Energy and Environmental Design (LEED) in the United States.

Certified collections can be found at https://spot.ul.com/.

Integrated Management System Certifications:



ISO 9001 certification: for corporate Quality system management. The certification, valid at an international level, concerns corporate management in its entirety, from research and development to production, and from distribution to customer support. This system certifies that the Company has implemented an internal quality management system.

The certification is available at www.porcelaingres.com/downloads/.



ISO 50001 certification: for organizations committed to addressing their impact, conserving resources and improving the bottom line through efficient energy management. The standard specifies the requirements for establishing, implementing, maintaining and improving an energy management system, whose purpose is to enable an organization to follow a systematic approach in achieving continual improvement of energy performance, including energy efficiency, energy security, energy use and consumption.

The certification is available at www.porcelaingres.com/downloads/.

Environmental Information and Labels:



Declare label: a badge for construction materials, essentially functioning as a voluntary self-disclosure program. This initiative furnishes details about the material's composition, final assembly locations, lifespan, end-of-life options, and overall adherence to pertinent Living Building Challenge® (LBC) requirements.

Accessible through a complimentary database, Declare® labels prove to be an essential tool for designers and architects, empowering them to specify products aligning with the criteria of key green building standards, including Core Green Building certifications, LBC, LEED, and WELL.

All our materials hold the classification of being "Red List Free," affirming their absence of chemicals listed in the Living Building Challenge's "Red List."

More info available at https://declare.living-future.org/products/ceramic-slabs.



ISO 14067 certification: is an international standard that outlines the principles and guidelines for measuring and communicating the carbon footprint of products. This certification focuses on assessing and managing the carbon emissions associated with all stages of a product's life cycle, from raw material extraction through production, distribution, use, and disposal.

The certification is available at www.porcelaingres.com/downloads/.



The **Cradle to Cradle** certification recognizes sustainable products, focusing on material health, recyclability, renewable energy, water use, and social fairness. It promotes a circular economy by encouraging reusable or upcycled products, reducing waste and environmental impact. **Available exclusively for our Great Collections (Large format)**.

The certification is available at https://c2ccertified.org/certified-products/porcelain-stoneware-slabs.



Porcelaingres[®]



Porcelaingres GmbH

Irisstraße 1 03226 Vetschau – Germany Tel. +49 (0)35433 / 597-0

GranitiFiandre spa

Via Radici Nord, 112 42014 Castellarano (RE) – Italy Tel. +39 0536 819611

Castellarano Showroom

Via Guido Reni 2 42014 Castellarano (RE) – Italy www.porcelaingres.com info@porcelaingres.com

Vetschau Showroom

Irisstraße 1 03226 Vetschau – Germany www.porcelaingres.com info@porcelaingres.com

A BRAND OF



Search "PORCELAINGRES" on your app store www.porcelaingres.com/pdfapp









Note: Technical Data updated on March 2025

Colors and decors reproductions are approximate. All rights are reserved. Total or partial reproduction of text or illustrations of this catalogue is prohibited and is subject to legal sanctions. Data were updated at the catalogue printing time; therefore, the listed data may alter.