Technical Data

Silk Stone | Summary




Silk Stone Collection - Colors: Light Ornament


Colors



Black Chiffon



Shantung Greige



White Satin



Dark Ornament

Velvet Brown



Vanilla Lace



Light Ornament

Technical features

Natural|R10 A+B|x6 mm



- 120×60 + Decor
- 120×30 + Decor
- 100×100
- 60×60 + Decor
- 60×30

Specials

- Mosaic
- Bullnose
- Step



40% Raw material from recycling process products assessed and found to comply with the LEED and BREEAM regulations.



click here for

Inspiration

Visit the collection webpage in other languages.

2 3

Silk Stone

Product details

		*							*	*	*	Slabs
Format (cm)	120×60	120×30	100 × 100	60×60	60×30	30×30	100 × 6,5	60×7	120×30	100 × 30	60×30	Variability
Thickness (mm)	¥ 6mm	x 6mm	x 6mm	 ¥6mm	¥ 6mm	¥ 6mm	¥ 6mm	¥ 6mm	¥ 6mm	¥ 6mm	¥ 6mm	Index
Finishing	Natural	Natural	Natural	Natural	Natural	Natural	Natural	Natural	Natural	Natural	Natural	The shade variation index is a rating to determine
Skid Resistance	R10 A+B	R10 A+B	R10 A+B	R10 A+B	R10 A+B	R10 A+B	-	-	R10 A+B	R10 A+B	R10 A+B	tile variation between
Description	-	-	-	-	-	Mosaic 4,7 × 4,7	Bullnose	Bullnose	Step with grooves	Step with grooves	Step with grooves	individual pieces of the same color group.
White Satin	X126350X6	X123350X6	X1010350X6	X600350X6	X630350X6	X370350X6	X1065350X6	X670350X6	X3213350X6	X3100350X6	X360350X6	V2 slightly different tone
Vanilla Lace	X126351X6	X123351X6	* X1010351X6	X600351X6	X630351X6	X370351X6	* X1065351X6	X670351X6	X3213351X6	X3100351X6	X360351X6	V2 slightly different tone
Shantung Greige	X126352X6	X123352X6	X1010352X6	X600352X6	X630352X6	X370352X6	X1065352X6	X670352X6	X3213352X6	X3100352X6	X360352X6	V2 slightly different tone
Velvet Brown	X126353X6	X123353X6	* X1010353X6	X600353X6	X630353X6	X370353X6	* X1065353X6	X670353X6	X3213353X6	X3100353X6	X360353X6	V3 different tone
Black Chiffon	X126354X6	X123354X6	X1010354X6	X600354X6	X630354X6	X370354X6	X1065354X6	X670354X6	X3213354X6	X3100354X6	X360354X6	V3 different tone
Light Ornament	X1266350X6	X1236350X6		X606350X6								V2 slightly different tone
Dark Ornament	X1266354X6	X1236354X6		X606354X6								V3 different tone
Features	GRIP+	GRIP+	GRIP+	GRIP+	GRIP+	GRIP+			GRIP+	GRIP+	GRIP+	
												Note
pieces - box	3	5	2	5	10	11	12	15	5	5	8	*Deceleration
boxes - pallet	32	40	26	32	40	-	-	-	-	-	-	*Production upon request
sqm - box	2,16	1,8	2	1,8	1,8	0,99	0,78	0,63	1,8	1,5	1,44	
sqm - pallet	69,12	72	52	57,6	72	-	-	-	-	-	-	
kg - sqm	14,35	14,35	14,06	13,89	13,89	1,25	0,92	0,59	5,17	4,2	2,5	
kg - box	30,996	25,83	28,12	25,002	25,002	13,75	11,04	8,85	25,85	21	20	

 $oldsymbol{4}$

Technical product features

Declared values of production

Compliance with standards

The surfaces complies with the European standards EN 14411 (group B1a) and international standards ISO 13006 Annex G.

- ISO 10545-2 (Determination of dimensions and surface quality)
- ISO 10545-3 (Determination of water absorption)
- ISO 10545-4 (Determination of modulus of rupture and breaking strength)
- ISO 10545-6 (Determination of resistance to deep abrasion for unglazed tiles)
- ISO 10545-8 (Determination of linear thermal expansion)
- ISO 10545-9 (Determination of resistance to thermal shock)
- ISO 10545-12 (Determination of frost resistance)
- ISO 10545-13 (Determination of chemical resistance)
- ISO 10545-14 (Determination of resistance to stains)

And it must also guarantee conformity with:

- DIN 51094 (lightfastness of the colours)
- DIN EN 16165 Annex B (to measure the surfaces suitability for laying in areas where people
 walk footwear. Defining the "R-value" of the surfaces according to the table below):

$$\alpha$$
 < 6° = not classified

 $6^{\circ} \le \alpha \le 10^{\circ} = R9$

 $10^{\circ} < \alpha \le 19^{\circ} = R10$

 19° < α ≤ 27° = R11

 $27^{\circ} < \alpha \le 35^{\circ} = R12$

 $\alpha > 35^{\circ} = R13$

 DIN EN 16165 - Annex A (to measure the surfaces suitability for laying in areas where people walk barefoot. Given an "A, B and C" value according to the table below):

 α < 12° = not classified

 $12^{\circ} \le \alpha < 18^{\circ} = A$

 $18^{\circ} \le \alpha < 24^{\circ} = B (A+B)$

 $\alpha \ge 24^{\circ} = C (A+B+C)$

Compliance with these characteristics is checked in accordance with the certified quality management system of the UNI-EN ISO 9001 standard in addition to being guaranteed by the manufacturer.

Porcelaingres surfaces are made with low environmental impact in accordance with LEED_ BREEAM guidelines by using both new strategies for the continuous improvement of environmental friendliness and the aim of reducing wasting of non-renewable resources, in addition to using natural raw materials commonly found in the environment and recycled materials.

Featu	ires	Norms	▲ Required standard	Declared values	
	water absorption	ISO 10545-3	≤ 0,5%	≤ 0,05%	
	sizes	ISO 10545-2	length and width ± 0,6% max thickness ± 5,0% max linearity ± 0,5% max wedging ± 0,6% max warpage ± 0,5% max	± 0,2% max ± 5,0% max ± 0,2% max ± 0,2% max ± 0,2% max	
1	bending strength	ISO 10545-4	≥ 35 N/mm²	> 48N/mm²	
(resistance to deep abrasion	ISO 10545-6	≤ 175 N/mm³	≤ 140 mm³	
(†)	thermal expansion coefficient	ISO 10545-8	testing method available	7 MK ⁻¹	
	thermal shock resistance	ISO 10545-9	testing method available	resistant	
	frost resistance	ISO 10545-12	no sample must show alterations to surface	frost resistance	
	chemical resistance	ISO 10545-13	no sample must show visible signs of chemical attack (acids-bases-additives for pools) except for products containing hydrofluoric acid and derivates.	unaffected	
	stain resistance	ISO 10545-14	unglazed tiles: testing method available	class 5	
0	colour resistance to light	DIN 51094	no sample must show noticeable colour change	no change in brightness or colour	
·	skid resistance average	DIN EN 16165 Annex B		R10 – natural	
W	coefficient of friction (μ)	DIN EN 16165 Annex A		A+B	

6

Certifications

Sensitivity towards ethycal, environmental, safety and quality concerns

Product Certifications:



LEED certification: is a global system used in 40+ countries to check if buildings are environmentally friendly. The LEED (Leadership in Energy and Environmental Design) It evaluates how well a building is sustainable in terms of the environment, society, and economy. The slabs in this tool have over 40% recycled material, following the ISO 14021 standard, ensuring the highest LEED points.

BREEAM certification is a widely used global standard that measures how buildings impact the environment. It has strictw rules and checks based on the latest technology and knowledge. The rating system demands certifications based on strict technical parameters and quality control.

You can find the updated list of certified collections at www.porcelaingres.com/downloads/.



UPEC classification associated with the QB certification mark attests to the compliance of floor and wall coverings with the technical requirements set out in certification reference documents. It assigns classifications of use indicating that the durability of a product is appropriate for use on specific types of premises.

The list of the certified products is available at http://evaluation.cstb.fr/



CE MARK - It indicates that Porcelaingres products comply with the requirements of 305/2011 UE directive - in particular with regard to health production and the users and consumers' safety - and may thus be freely circulated on the Community market. For the declarations of conformity of each single product, please refer to: www.porcelaingres.com/downloads/.



The China Compulsory Certificate mark, commonly known as a CCC Mark, is a compulsory safety mark for our Great Format products imported, sold or used in the Chinese market.

The certification is available at www.porcelaingres.com/downloads/.



EPD (Environmental Product Declaration): a voluntary type III product declaration, based on analysis of the product life cycle (with a "from cradle to grave" approach) in accordance with the EN 15804 standard. This declaration is drawn up with reference to the guidelines of the UNI EN ISO 14040 standard and the specific PCR (Product Category Rules). This document describes the environmental impact linked to the entire life cycle of a specific quantity of product. Our Company was the first to certify its products (see www.environdec.com) with specific EPD, validated by an independent third-party Body.

The certification is available at www.porcelaingres.com/downloads/.



GREENGUARD certification ensures indoor products have minimal emissions of volatile substances for healthier environments. GREENGUARD Gold Certification considers safety for sensitive individuals and approves products for use in places like schools and healthcare facilities. Widely recognized globally in sustainable building programs, it is referenced by The Collaborative for High Performance Schools (CHPS) and Leadership in Energy and Environmental Design (LEED) in the United States.

Certified collections can be found at https://spot.ul.com/.

Integrated Management System Certifications:



ISO 9001 certification: for corporate Quality system management. The certification, valid at an international level, concerns corporate management in its entirety, from research and development to production, and from distribution to customer support. This system certifies that the Company has implemented an internal quality management system.

The certification is available at www.porcelaingres.com/downloads/.



ISO 50001 certification: for organizations committed to addressing their impact, conserving resources and improving the bottom line through efficient energy management. The standard specifies the requirements for establishing, implementing, maintaining and improving an energy management system, whose purpose is to enable an organization to follow a systematic approach in achieving continual improvement of energy performance, including energy efficiency, energy security, energy use and consumption.

The certification is available at www.porcelaingres.com/downloads/.

Environmental Information and Labels:



Declare label: a badge for construction materials, essentially functioning as a voluntary self-disclosure program. This initiative furnishes details about the material's composition, final assembly locations, lifespan, end-of-life options, and overall adherence to pertinent Living Building Challenge® (LBC)

Accessible through a complimentary database, Declare® labels prove to be an essential tool for designers and architects, empowering them to specify products aligning with the criteria of key green building standards, including Core Green Building certifications, LBC, LEED, and WELL.

All our materials hold the classification of being "Red List Free," affirming their absence of chemicals listed in the Living Building Challenge's "Red List."

More info available at https://declare.living-future.org/products/ceramic-slabs.



volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

8

Porcelaingres[®]



Porcelaingres GmbH

Irisstraße 1 03226 Vetschau – Germany Tel. +49 (0)35433 / 597-0

GranitiFiandre spa

Via Radici Nord, 112 42014 Castellarano (RE) – Italy Tel. +39 0536 819611

Castellarano Showroom

Via Guido Reni 2 42014 Castellarano (RE) – Italy www.porcelaingres.com info@porcelaingres.com

Vetschau Showroom

Irisstraße 1 03226 Vetschau – Germany www.porcelaingres.com info@porcelaingres.com

A BRAND OF



Search "PORCELAINGRES" on your app store www.porcelaingres.com/pdfapp









Note: Technical Data updated on December 2023

Colors and decors reproductions are approximate. All rights are reserved. Total or partial reproduction of text or illustrations of this catalogue is prohibited and is subject to legal sanctions. Data were updated at the catalogue printing time; therefore, the listed data may alter.